

EZE-Space™ Portable Room Dividers

Suggested Specification



- Sound Absorbing
- Tackable for Display of Materials
- Self-Leveling Casters
- Collapses and Nests for Compact Storage
- Ships Fully Assembled; No Installation or Assembly Required
- Provides Privacy and Noise Reduction
- Durable Frame Creates Strength and Resists Scratching

IPC.3075/REV.1

Inprocorp.com • 800.222.5556 • 262.679.9010
World Headquarters S80 W18766 Apollo Drive, Muskego, WI 53150 USA

CLICKEZE® •
PRIVACY SYSTEMS
A DIVISION OF INPRO®

EZE-Space™ Portable Room Dividers

Suggested Specification

Specifier Note: Specifications provided by:
Clickeze, a Division of Inpro Corporation
S80 W18766 Apollo Drive, Muskego, WI 53150
USA
Inprocorp.com
800-222-5556

PART 1 - GENERAL

1.01 SUMMARY

A. Portable Room Dividers

1.02 SECTION INCLUDES

A. EZE-Space™ Portable Room Dividers for privacy and decoration

1.03 REFERENCES

- A. American Association of Textile Chemists and Colorists (AATCC)
- B. American Society for Testing and Materials (ASTM)
- C. National Fire Protection Association (NFPA)

1.04 SYSTEM DESCRIPTION

A. Performance Requirements: Provide EZE-Space™ Portable Room Dividers that conform to the following requirements of regulatory agencies and the quality control of Inpro Corporation.

1. Fire Performance Characteristics: Provide EZE-Space™ Portable Room Dividers conforming with the NFPA Class A fire rating. Surface burning characteristics as determined by ASTM E-84 shall be flame spread of 25 or less and smoke developed of 450 or less.
2. Colorfastness: Fabric, AATCC16 option 3- Class 4.0
3. Fungal and Bacterial Resistance: Provide portable room divider panels that do not support fungal or bacterial growth as tested in accordance with ASTM G-21 and ASTM G-22.
4. Sound Absorption: Provide portable room dividers that have a noise reduction coefficient of 45. (6'-0" high panel tested. Other heights will have different results.)

1.05 SUBMITTALS

- A. Product Data: Manufacturer's printed product data for each type of EZE-Space™ Portable Room Dividers specified.
- B. Samples: Verification samples of EZE-Space™ Portable Room Dividers colors swatches.

1.06 DELIVERY, STORAGE AND HANDLING

- A. Deliver materials in unopened factory packaging to the jobsite. Do not lay flat; must ship upright.
- B. Inspect materials at delivery to assure that specified products have been received.
- C. Store in original packaging in a climate controlled location away from direct sunlight.

1.07 PROJECT CONDITIONS

A. Environmental Requirements: Products must be used in an interior climate controlled environment.

1.08 WARRANTY

A. Standard Inpro Limited Lifetime Warranty against material and manufacturing defects.

PART 2 - PRODUCTS

2.01 MANUFACTURER

A. Manufacturer/Distributor: Clickeze ,
Inpro Corporation, PO Box 406 Muskego, WI 53150
USA;
Telephone: 800.222.5556, Fax: 888.715.8407,
www.inprocorp.com
B. Provide all EZE-Space™ Portable Room Dividers and Privacy Systems from a single source.

2.02 MANUFACTURED UNITS

Specifier Note: Delete or include items below in red as required by this project.

A. Portable Room Dividers

1. EZE-Space™ Portable Room Dividers

- a. Provide EZE-Space™ Portable Room Dividers with .75" (19 mm) thick panels. Panel shall be constructed of a 20 gauge galvanized steel frame with a ½" (12.7mm) sound trapping honeycomb core that has a nonwoven fiberglass facing. Panel shall be covered with a tackable 10-pound fiberglass mat and a fabric/vinyl outer covering. Outer trim shall be a scratch-resistant 20-gauge powder coat steel. End frames shall be 14 gauge powder coat steel.
- b. Standard features include, a stable support base, full-length hinges, self-leveling casters, sound absorbing panels and tackable panels.
- c. Options: **Multi-unit connector, chrome plated latches installed on the end frames of a room divider allows two or more dividers to be joined end-to-end.**

2. Sizes:

- a. Panel thickness: .75" (19mm)
- b. Heights: **4'-0" (1.22m), 5'-0" (1.52m), 6'-0" (1.83m), 6'-8" (2.03m), 7'-4" (2.24m) and 8'-0" (2.44m)**
- c. Number of Panels, Extended Lengths:
 1. Double End Frame Unit:
3 Panel, 5'-9" (1.75m)
5 Panel, 9'-5" (2.87m)
7 Panel, 13'-1" (3.99m)
9 Panel, 16'-9" (5.11m)
11 Panel, 20'-5" (6.22m)
13 Panel, 24'-1" (7.34m)

2. Single End Frame Unit (6' Height only)

- 3 Panel, 5'-8" (1.73m)**
- 4 Panel, 7'-6" (2.29m)**
- 5 Panel, 9'-4" (2.84m)**
- 6 Panel, 11'-2" (3.40m)**
- 7 Panel, 13'-0" (3.96m)**

Folded footprint (maximum): 25" (.635m) x 39" (.991m)

2.03 MATERIALS

- A. Galvanized Steel: Panel frame shall be 20 gauge galvanized steel.
- B. Core shall be sound absorbing honeycomb
- C. Fiberglass facing shall be non-woven.
- D. Fiberglass mat shall be 10-pound
- E. Outer covering shall be 100% recycled polyester fabric or vinyl wall covering.

2.04 FINISHES

- A. Color of end frames and outer trim shall be powder-coat black.
- B. Color or pattern of the EZE-Space™ Portable Room Divider panels to be selected by the architect from the EZE-Space™ finish selection.

PART 3 - EXECUTION

3.01 EXAMINATION

- A. Examine areas and conditions in which the EZE-Space™ Portable Room Divider will be installed.
 1. Complete all finishing operations, including painting.

3.02 PREPARATION

- A. General: Prior to installation, make sure area is free from dust, debris and loose particles.

3.03 INSTALLATION

- A. General: Unpack EZE-Space™ Portable Room Dividers. No assembly is required.

3.04 CLEANING

- A. Dust surfaces to keep clean and free of dust.

END OF SECTION

Inprocorp.com • 800.222.5556 • 262.679.9010

World Headquarters S80 W18766 Apollo Drive, Muskego, WI 53150 USA

CLICKEZE®
PRIVACY SYSTEMS
A DIVISION OF INPRO®